

IN THE SPECIFICATION:

The specification as amended below with replacement paragraphs shows added text with underlining and deleted text with ~~striketrough~~.

Please REPLACE the paragraph beginning at page 9, line 8, with the following paragraph:

The video captured by the security cameras 6, 8 is designed to be recorded in multiple as a failsafe against loss of recordings. For example, in the embodiment of FIG. 5A, the media for recording video captured by the security cameras 6, 8 includes a CD-R drive 13 and a hard disk drive (hereinafter referred to as the "HDD") 14 built into the controller 40 and a video tape recorder (hereinafter referred to as a "VTR") 15 provided outside of the ATM 10. The image recorded in the VTR 15 can be monitored by a supervisor etc. by provision of a video monitor outside of the ATM 10. In this way, in this embodiment, even if two of the three recorders break down, it is possible to record and store the image by the remaining (i.e., third) one.

Please REPLACE the paragraph beginning at page 10, line 4, with the following paragraph:

Therefore, in the ATM 10 of the present invention, by operating both the conventionally provided security camera 6 and the security camera 8 newly provided in the present invention, it is possible to record both the image of the state of the surroundings including the upper torso of the customer 7 withdrawing or depositing cash and the image of the hand of the customer 7 at the time of withdrawal. Therefore, in the ATM 10 of the present invention, it is possible to kept keep a surveillance record of a customer 7 unintentionally forgetting to take his or her cash etc. Further, the security camera 8 installed in the ATM 10 of the present invention is not visible until the shutter 2A of the bill receptacle 2 opens, and, once the shutter 2A opens, the attention of the customer 7 shifts to the bills stored in the bill holder 2B, so its existence is hard for a customer 7 to notice.